

LED Wall Light

RBR24LED

Please read instructions before commencing installation and retain for future reference.

Wall light for indoor or outdoor use, with sleeve for recess mounting in wall, 5mm thick glass, 2 cable entries for loop-in/loop-out wiring and 24 light emitting diodes and stainless steel front trim

Specification:

Protection against electric shock: Class 1 must be earthed

Supply: 230/240V 50Hz

Temperature range: $-20^{\circ}\text{C} < t_a < 40^{\circ}\text{C}$

Terminals suitable for cable sizes from 0.75mm^2 to 1.5mm^2 .

Sleeve dimensions: 226mm x 70mm x 80mm deep

Power consumption: approx 6W



Suitable for mounting on normally flammable surface, e.g. wooden decking

Ingress protection: IP67, dust and water proof

Complies with EN60598-1, EN55015, EN61547, EN61000-3-2/-3

! Electrical products can cause death or injury, or damage to property. If in any doubt about the installation or use of this product, consult a competent electrician.

Installation:

- 1 Ensure mains supply is switched off before commencing work.
- 2 Check for location of buried cables before making recess and fitting sleeve. In the recess, the front edge of the sleeve should be set back about 1mm from wall face.
- 3 Disassemble fitting, removing front bezel and glass, and loosen the printed circuit board carrying the LED's to access the terminal block. (If using only one cable entry gland, check that the membrane on the other is still intact)
- 4 Introduce supply cable(s) and connect Live, Neutral and Earth respectively. Tighten cable gland(s) to ensure a waterproof seal.
- 5 Re-fit circuit board, locate fitting in the sleeve and secure with the screws provided.
- 6 Finally, re-fit glass and front bezel, tightening screws securely to complete installation.

• The installation must be carried out by an electrician. •